

SERIE: PULL REF. B-003087



Descripción

Collection of LED outdoor wall lights, equipped with high performance light emitting diode. Body made of aluminum injection, diffuser in PC opal. Protection against the penetration of solid and liquid particles. Allows its installation outdoors. Pre-wired luminaire.


Colección de apliques de exterior LED, equipados con diodo emisor de luz de alto rendimiento. Cuerpo fabricado en inyección de aluminio, difusor en PC opal. Protección contra la penetración de partículas sólidas y líquidas. Permite su instalación al aire libre. Luminaria precableada.



FINISHES AVAILABLE

DARK GREY MATT BLACK

ENERGY EFFICIENCY



TECHNICAL DATA SHEET

TEOHMORE DATA ONCE I	
Application	SURFACE
IP Rating	IP54
Light source	LED 2835
Wattage	12 W
Chip Brand	OSRAM
CCT Kelvin	3000 / 4000 / 5000K
Lumen	530
IF—VF	200 mA—27-40V
C.R.I	≥ 80
SDCM	≤ 5
IK	08
Beam Angle	205 °, 96 °
Input Voltage - Frequency	100-240V ~ 50/60Hz
Electrical Classification	I
Lifespan	25000h. L70B50
Driver	Inside - Included
Power Factor:	0.9
Power Efficiency	84%
Measure mm	260 x 130 x 115.5 mm.
Working humidity	10%∼90%RH
Weight Kg.	0.9
Working humidity	-30°∼+45°
Lighting distance	3 m
Certificates - Standard	CE - IEC 60598-1/IEC 62031
Warranty years	3
MATERIALES / ACABADOS	
Structure material	High quality aluminum
Diffuser Materilal	PC
Structure finishing	Anti - UV powder coating finish
The state of the s	

IBERLAMP reserves the right to carry out the appropriate technical modifications in order to improve the performance of the product.
We recommend consulting with the sales team to clarify any doubts.

Opal White

Diffuser finishing



Photometric Results

CIE Class:	Direct
Total Rated Lamp Lumens:	530 lm.
Measurement Flux:	530 lm.
Efficiency:	57.5 %
Downward Ratio:	47.2%
Upward Ratio:	10.3%
Luminaire Efficiency Rating (LER):	44.2
Central Intensity:	106.8 cd.
Max. Intensity:	106.8 cd.
Pos. Of Max Intensity:	H0.0 V-35.5
IES File Name	B-003087

